

# LED STANDARD FLOOD LIGHT - C

## FEATURES & BENEFITS

- Modular design allows for easy installation, replacement and maintenance. This design also creates a chimney effect which provides exceptional thermal management.
- Corrosion resistant polyester powder painted 100µm thickness.
- Meets a 1000-hour salt spray certification per ASTM B117/ ISO 9227:2012.
- Over 20 optical lenses are available for virtually any application.
- Extremely flexible with full 360 degree rotation.
- Multiple smart lighting control options are available, e.g. photocell, motion sensor, DALI, 1-10V.
- 5 years limited warranty.
- NICHIA 3535 LED Chips / Philips Advance Xitanium LED Driver.


## CERTIFICATIONS

UL/ CUL/ LM79/ SAA/ ENEC/ CB/ CE/ ErP/ RoHS/ IK08

## TECHNICAL PARAMETERS

<b>Power</b>	40-320W
<b>Input</b>	120-277VAC or 220-240VAC or 347-480VAC
<b>PF</b>	>0.95
<b>THD</b>	<20%
<b>L85</b>	>60,000H
<b>Operating Temperature</b>	-40°C ~ +50°C
<b>Efficacy</b>	125 lm/W
<b>ANSI CCT</b>	3000K/4000K/5000K/5700K
<b>Min CRI</b>	70* or 80 or 85
<b>IP Rating</b>	IP67
<b>SPD</b>	Optional
<b>DALI</b>	Optional
<b>1-10V</b>	Optional
<b>Photocell</b>	Optional
<b>Smart Control</b>	Optional
<b>Optic (IESNA)</b>	Type I, Type II, Type III, Type IV, Type V
<b>Color Options</b>	Grey/Black/Bronze/White

\* Standard



## ORDERING INFORMATION

Example : APSFL-C-160-A1-50K-T5V-BK-1

Fixture	Power (Watts) (40W/module)	Voltage	Color Temperature (CCT)	Light Distribution (Lens Type)	Fixture Color	Mounting Options (Brackets)	Lighting Controls	Accessory Info
APSFL-C - Standard Flood Light	40 - 5,000 lumens 60 - 7,500 lumens 80 - 10,000 lumens 90 - 11,250 lumens 120 - 15,000 lumens 150 - 18,750 lumens 160 - 20,000 lumens 180 - 22,500 lumens 200 - 25,000 lumens 210 - 26,250 lumens 240 - 30,000 lumens 270 - 33,750 lumens 280 - 35,000 lumens 300 - 37,500 lumens 320 - 40,000 lumens	A1: 120-277V AC  B4: 347-480V AC	30K - 3000K 40K - 4000K 50K - 5000K 57K - 5700K	T1M1 - Type I Medium T2M1 - Type II Medium T3M1 - Type III Medium T3L1 - Type III Long T4S1 - Type IV Short T4M1 - Type IV Medium T5U - 10° T5V - 25° T5W - 40° T5S - 60° T5M - 90° T5L - 120° T5X - 150° T5D - Type V Diffuser	GR - Grey BK - Black BZ - Bronze WH - White CU - Custom*	Y - Yoke Mount  T - Tenon Mount	00 Not required 01 Photocell 02 Motion Sensor 03 Photocell + Motion Sensor 04 DALI 05 1-10V dimming	3/5/7 pin receptacle 10KA / 20KA Surge Protection Device Safety Cable Side Shield

\*Extra cost for custom color

\*\*Note this after lens type.