

# LED STANDARD HIGH BAY



## FEATURES & BENEFITS

- Modular design allows for easy installation, replacement and maintenance.
- Corrosion resistant polyester powder painted 100µm thickness.
- Meets a 1000-hour salt spray certification per ASTM B117/ ISO 9227:2012.
- Over 20 optical lenses are available for virtually any application.
- Surface mount.
- 3/4" pendent rod option available.
- Multiple smart lighting control options are available, e.g. photocell, motion sensor, DALI, 1-10V.
- 5 years limited warranty.
- Nichia 3535 LED Chips / Philips Advance Xitanium LED Driver.


## CERTIFICATIONS

UL/ CUL/ LM79/ SAA/ ENEC/ CB/ CE/ ErP/ RoHS/ IK08

## TECHNICAL PARAMETERS

<b>Power</b>	30-320W
<b>Input</b>	120-277VAC or 220-240VAC or 347-480VAC
<b>PF</b>	>0.95
<b>THD</b>	<20%
<b>L85</b>	>60,000H
<b>Operating Temperature</b>	-40°C ~ +50°C
<b>Efficacy</b>	125 - 135 lm/W
<b>ANSI CCT</b>	3000K/4000K/5000K/5700K
<b>Min CRI</b>	70* or 80 or 85
<b>IP Rating</b>	IP67
<b>SPD</b>	Optional
<b>DALI</b>	Optional
<b>1-10V</b>	Optional
<b>Photocell</b>	Optional
<b>Smart Control</b>	Optional
<b>Optic (IESNA)</b>	Type I, Type II, Type III, Type IV, Type V
<b>Color Options</b>	Grey/Black/Bronze/White

\* Standard



## ORDERING INFORMATION

Example : APSHB-160-A1-50K-T5L-BK-1

Fixture	Power (Watts) (40W/module)	Voltage	Color Temperature (CCT)	Light Distribution (Lens Type)	Fixture Color	Mounting Options (Brackets)	Lighting Controls	Accessory Info
APSHB - Standard High Bay	30 - 3,900 lumens	A1: 120-277V AC B4: 347-480V AC	30K - 3000K	T1M1 - Type I Medium	GR - Grey BK - Black BZ - Bronze WH - White CU - Custom*	D - Yoke Mount P - Pendant Mount WI - Wire Mount	00 Not required	Emergency Battery Backup
	40 - 5,200 lumens		40K - 4000K	T2M1 - Type II Medium			01 Photocell	
	60 - 7,500 lumens		50K - 5000K	T3M1 - Type III Medium			02 Motion Sensor	
	80 - 10,400 lumens		57K - 5700K	T3L1 - Type III Long			03 Photocell + Motion Sensor	
	120 - 15,600 lumens		T4S1 - Type IV Short	04 DALI				
	160 - 20,800 lumens		T4M1 - Type IV Medium	05 1-10V dimming				
	200 - 26,000 lumens		T5U - 10°					
	240 - 31,200 lumens		T5V - 25°					
	280 - 36,400 lumens		T5W - 40°					
	320 - 41,600 lumens		T5S - 60°					
			T5M - 90°					
			T5L - 120°					
	TSX - 150°							
	T5D - Type V Diffuser							

\*Extra cost for custom color

\*\*Note this after lens type.